



# ALBRO

# Total resistance

- **From the first to the last day.**

- **Guaranteed durability.**

Higher thickness of the pan to increase its durability.

UV rays, detergents and disinfectants high resistant plastic.

We offer a 10-year guarantee\*. (\* With depreciation).

- **Control unit with LED light option.**

Control unit is available with LED light kit, to attract the birds to guarantee a completely filled feeding line.



 **GROWKET**  
SYMAGA GROUP

TECHNICAL INFORMATION	
<b>FEEDER</b>	
High	79 mm
Diameter	330 mm
Perimeter	1036mm
Material	Polypropylene
Capacity of 1-7 levels	1-1,4 kg
<b>TRANSPORT</b>	
Feeding hopper 75	Content 75 L
Feeding hopper 150	Content 150 L
Maximum length of the system	150m
Galvanized tube with 3 ó 4 holes	Diameter 45 mm
Pipes length	3000 mm o 3050 mm useful
Drive unit with gear motor	0.37/0.75kw, 220/380v, 50-60 Hz phases, 300 rpm
Conveying capacity	Approx. 450 kg/h
Size of pellets	Up 4 mm
Suspension distance	3m maximum
<b>BROILER GROWING AD LIBITUM FEEDING*</b>	
Farm width	Nº of feeders lines *
9-12	2
12-15	3
15-18	4
Final weight kg	Birds/Feeders **
Until 2.0	60-90
Until 3.0	55-75
Until 4.0	45-65

\* 1 feed line per 4-5m farm width.

\*\* Mean values which may vary depending on the breed, density and climate. Also observe country specific legal parameters.

